

10/502492  
DT15 Rec'd PCT/PTO 23 JUL 2004

IN THE UNITED STATES PATENT AND TRADE MARK OFFICE

VERIFICATION OF TRANSLATION

I, Michael Wallace Richard Turner, Bachelor of Arts, Chartered Patent Attorney, European Patent Attorney, of 1 Horsefair Mews, Romsey, Hampshire SO51 8JG, England, do hereby declare that I am conversant with the English and German languages and that I am a competent translator thereof;

I verify that the attached English translation is a true and correct translation made by me of the attached specification in the German language of International Application PCT/EP03/00638;

I further declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment or both under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Date: June 17, 2004

MWR Turner  
M W R Turner

Aloys WOB BEN

Argenstrasse 19, 26607 Aurich

---

Vehicle

---

5           The present invention concerns a motor vehicle comprising at least one electric motor, an energy storage device for providing drive energy for the electric motor, a plug connector connected to the energy storage device for connection to a current source and a control means for controlling the flow of current from the current source to the energy storage device.

10           Such vehicles have already been known for some time and are eminently suitable for journeys over short and medium distances. In order to make such a vehicle usable the available energy storage device has to be charged up. When the vehicle has covered a certain distance the storage device has to be charged up again. In that case, a careful driver will re-  
15   charge the energy storage device after each journey in order always to have at his disposal the greatest possible range.

          As journeys with the vehicles - like also with all other vehicles - cannot always be exactly planned in advance, it can happen with such a procedure that the energy storage device of the vehicle is to be charged up  
20   precisely when the cost of the energy is at its highest, and when in addition the supply network is most heavily loaded, for example during what is referred to as a midday peak.

          That is disadvantageous both because of the high price of buying the energy while it is also disadvantageous because of the loading on the  
25   supply network which in any case is already highly loaded.

          Therefore the object of the invention is to provide a motor vehicle which can contribute to moderating the loading at consumption peaks in the network.

          That object is attained by a motor vehicle of the kind set forth in the  
30   opening part of this specification, in that the control means permits a flow of current from the energy storage device to the current source. In that way a flow of current can take place from the energy storage device of the

motor vehicle back into the network and can thus contribute to covering the peak demand.

In a preferred embodiment of the invention the flow of current from the energy storage device to the current source, that is to say for example  
5 into the current network, is controlled in such a way that a predeterminable residual amount of electrical energy is retained in the storage device, by the control means interrupting the flow of current to the network when said predetermined residual charge amount is reached. For that purpose, there is provided a device for detecting the amount of charge in the energy  
10 storage device.

In a preferred development of the invention the control means communicates with the network through a communication device so that the draw of energy can be controlled in the optimum fashion from the network, in dependence on the location of the motor vehicle and the  
15 available amount of charge.

Particularly preferably the control means is designed in such a way that it includes a clock or is connected to a clock. In that way the control means can operate in such a fashion that charging and discharging operations take place in predeterminable periods of time. It is possible in  
20 that way to provide that the energy storage device is preferably charged up at night when on the one hand the loading on the supply network is low and on the other hand the costs of charging it up are low, while discharging preferably takes place at times when relieving the load on the supply network makes sense and the costs of the energy are higher than the costs  
25 during the charging procedure. In that way it is also possible to achieve an economic advantage, from the point of view of the operator of the vehicle, besides relieving the load on the supply network.

An embodiment of the invention is described in greater detail hereinafter with reference to the Figure.

30 The Figure shows a simplified block circuit diagram of the arrangement according to the invention. Reference 1 denotes a frame which includes those components which are associated with the motor vehicle. Accordingly the motor vehicle includes a control means 10. The

control means 10 is connected to an energy storage device 20, a drive motor 40 and a releasable connector 50 which for example is in the form of a plug connector. There is also a connection between the connector 50 and a current source 30 which here is indicated in the form of an electrical  
5 current supply network.

In order to provide sufficient energy for operation of the motor vehicle 1, the control means 10 monitors the charge condition of the storage device which can be for example a battery but also a capacitor storage device or the like. When the storage means 10 recognises that  
10 charging of the storage device 20 is required, the control means allows a flow of current from the network 30 to the storage device 20 by way of the connector 50 and the storage device is charged up. It will be appreciated that, in that case, the control means 10 can also take account of the corresponding charging characteristics of the storage device so that  
15 overcharging of the storage device is reliably prevented.

The control means can also permit charging in a predeterminable first period of time. That makes it possible for the storage device 20 to be preferably charged up at night when on the one hand the price of the electric current is low and thus the costs involved in charging the storage  
20 device also remain comparatively low while on the other hand the loading on the supply network 30 is not very high. In addition the control means can be so designed that it permits a flow of current from the storage device 20 by way of the plug connector 50 into the network 30.

In that respect the amount of charge which can be delivered can be  
25 limited by a predeterminable residual amount of charge at the storage device 20.

In that way for example after a journey to the place of work, with the storage device 20 fully charged, the energy which is still present in the storage device can be fed into the network 30 again if the demand is  
30 particularly high, for example for the midday peak. However the control means interrupts the flow of current from the storage device 20 into the network 30 when a predeterminable residual amount is reached, so that at

any event an adequate amount of energy in the storage device for the return journey in the evening is guaranteed.

It will be appreciated that the current which is fed into the network at the peak time is to be suitably reimbursed so that, besides the aspect of  
5 relieving the load on the network, there is also an economic advantage to be achieved.

It was proposed in accordance with the invention that a vehicle with an electrical energy storage device is also to be used as an energy source for a power supply network from which the vehicle possibly draws its  
10 energy.

As is known the power demand during the day is markedly higher than the power demand at night. Thus for example the power demand in a public power supply network rises from a low point at between 1 o'clock and 4 o'clock at night in the morning (morning peak), reaches its highest  
15 level (midday peak) around midday and then decreases in the evening again until it reaches its low level in the middle of the night. As therefore the energy demand at night is markedly lower than the usual available energy supply and the consumers also take night-time power, it is markedly lower in price than the price for daytime power.

20 An electrical power supply network then has to be designed in such a way that it has to cover without any problem not only the demand at night, but also the demand at the highest daytime peaks. In regard to the electrical supply utilities, that means that a large number of electrical energy generators must be provided, which reliably guarantee that such a  
25 demand is met, even at very high midday peaks (on a cold winter's day).

Now, at this point, the invention proposes that an electric vehicle which usually draws its electrical energy from an electrical supply network and which therefore also has suitable connections with a connection to an electrical power supply network can no longer be charged up with the  
30 electrical energy from the power supply network, but if necessary, at a given moment in time, can also feed energy that is not required, into the supply network.

If it is first assumed that the vehicles have to be used by the population working on weekdays, only in the periods between 7 am and 8.30 am and about 4.30 pm and 6.30 pm, such a motor vehicle is in a parking place, without being used, for most of the day. Charging up the energy storage device of the electric vehicle at night at the home of the owner of the vehicle is not a problem and has also already been done. What is new however is the proposal according to the invention that, after the motor vehicle has reached the place of work, it is also connected to an electrical current network in order then to provide the energy which is necessary as required, for the peak power times.

If in that case the motor vehicle has batteries which discharge/charge up very quickly, it is therefore possible, just with a number of 500 - 1000 units of that nature, to provide a very high level of feed-in power for the network.

The particular advantage for the electrical power supply utility is that it can have recourse to an electrical energy storage device which it has not paid for itself and for the maintenance of which it also does not have to bear responsibility. From the point of view of the user of the vehicle, the advantage of the invention is that, for example at the midday time when therefore he does not in any case require his motor vehicle because he is at his place of work, he virtually rents the storage device, which is still well filled, of his vehicle, to the electrical power supply utility, and can sell the energy contained therein. The consumer can therefore feed the electrical energy from his vehicle into the power supply network at midday and will receive a comparatively good price, while at night he has to arrange for charging up his vehicle at a good price (night-time current).

It will be appreciated that, in accordance with the invention, it is also provided that the electrical storage device of the vehicle does not fall below a given minimum level and, if necessary, the electrical storage device of the vehicle can also be charged up again after the midday peak, more specifically when the demand in the network has decreased again in the afternoon.

It can however also be provided that the user individually adjusts his vehicle in such a way that, in the evening, he has sufficient energy to complete his journey home (minimum content of energy with a sufficient level of certainty of arriving home) so that total charging of the storage device is only effected again during the following night, with the corresponding night-time current.

Therefore, by means of suitable programming (possibly also by way of remote input (the user employing his cellular phone)), the user of the vehicle can also predetermine the periods or the times within which only discharging of his storage device can take place.

The invention is suitable in particular in conurbations where there are large parking lots and large multi-storey car parks. The invention seems to be quite particularly suitable for use in multi-storey car parks at airports, in particular those airports which carry holiday traffic, for at such car parks there are often many thousands of private cars which are completely unused for an average of 7 - 14 days. During that period, a suitable power management system at the corresponding connection of the vehicles, if they are in the form of electric vehicles according to the invention, could be made available to the electrical power supply network which discharges the respective storage devices of the vehicles at peak times and charges the storage devices of the vehicles with electrical energy again at the periods of lower demand.

The invention is described in greater detail hereinafter by means of an embodiment illustrated in the drawing.

Herein Figure 1 - as described - shows an overview of the connection of a vehicle according to the invention to an electrical power supply network. Figure 2 shows a conventional day chart of the power demand in the case of an electrical power supply utility. Figure 3 shows a charge condition time table with the charge condition of a vehicle according to the invention.

The electrical storage device of the vehicle 1 is equipped with a suitable electronic control means (power management system) which

makes it possible to trigger and control not only electrical charging but also discharging of the storage device.

In addition the power management system can also be programmed in such a way that discharging is possible only for a quite specific time which is predetermined by the user. For example, it can be provided that discharging and thus a feed of power into the electrical energy supply network is possible only during the time from 10 am to 3 pm, otherwise, when the vehicle is connected to the supply network, the battery is being correspondingly charged.

The power management system can also be programmed in such a way that, when discharging is effected in the period from 7 am to 4 pm, charging does not take place straightaway, but charging occurs only in the night period between 12 midnight and 4 am, that is to say when particularly appropriate night-time current is to be taken from an electrical supply network.

In addition the power management system of the vehicle can be programmed in such a way that basically a minimum amount of charge remains in the storage device, that is to say cannot be fed into the supply network, in order in any case to ensure that the user can properly travel the distance that he wants, in his vehicle, that is to say for example the journey home from his place of work.

It will be appreciated that still further programming modes are possible, so that the power management system can also be set by the user himself, in just any conceivable manner, according to his respective wishes, while if necessary there is the possibility of a feed into the power supply network.

As can be seen from Figure 2 the current/energy demand of an electrical supply utility (ESU) is not distributed linearly over the entire day, but rises from a lowest point early in the morning (about 1 am to 3 am), reaches a first morning peak, then later reaches the so-called midday peak, that is to say its highest point, and then decreases irregularly towards the night again. The electrical power supply network which has the responsibility of always making sufficient electrical energy available to the



consumers connected to the electrical supply network, even at peak times, not only has to ensure that appropriate energy is fed into the supply network, but also that there is always so much energy in readiness that, at all times, that is to say even at extraordinary peak times, the responsibility  
5 of providing an electrical supply with electrical energy at a constant voltage level and a constant frequency is always met. It is apparent that a large number of control interventions both on the producer side and also in terms of the distribution of electrical energy is already required nowadays for that purpose.

10         Figure 3 shows a configuration by way of example of the charge condition of the electrical storage device of a vehicle according to the invention. In the electrical storage device which was charged with night-time current during the night, and which therefore exhibits a one hundred percent filling (I), that charge condition falls, in the morning journey (II) to  
15 the place of work. When the place of work is reached (III) and the vehicle is connected by way of the electric lines to the electrical supply network, the charge condition is possibly returned to one hundred percent again. At the midday time (IV), that is to say when the midday peak occurs (see Figure 2), a large part of the stored electrical energy in the storage device  
20 is fed into the connected electrical supply network so that the charge condition correspondingly falls within a very short time to a prescribed minimum (V). That minimum has been set by the user or the vehicle manufacturer (it can also be set in another fashion) and should be sufficient for the vehicle to be able to still make the journey home, without charging  
25 it up beforehand.

       In the illustrated example however the charge condition can also be increased again in the afternoon (VI) by taking energy from the supply network and during the journey home (VII) the charge condition further falls again. When the electric vehicle is subsequently connected to the  
30 electrical power supply network the charge condition can be restored to the prescribed value (100%) again in the evening/at night (VIII).

       It should be pointed out once again that the configuration as set forth in Figure 3 is given purely by way of example.

If the electric vehicle has a suitable input surface, the user of the vehicle can execute a large number of setting adjustments.

Thus for example, by means of a suitable input, the user can predetermine the periods of time, within which only discharging of the electrical storage device can take place at all, when connected to an electrical supply network.

As corresponding documentation of the charging and discharging operations shows, the user, even after several days, can still see when and what amounts of energy were fed into the electrical supply network.

Besides the electrical storage device, for example a lithium battery or another storage technology, the vehicle according to the invention has a suitable power management program for controlling the charge condition of the electrical storage device and for evaluation of the inputs of the user and also for documentation purposes.

In addition the vehicle can have a suitable data interface (besides receiver/transmitter for wireless (cellular phone) control) so that the vehicle can send to or receive from a suitable interface of the electrical power supply utility, all data which are necessary for charging and also for discharging (feed into the network).

That facilitates documentation of the respective discharging and charging conditions/times and billing thereof. In regard to billing, account is to be taken of the fact that current which is fed into the network at the midday peak can be reimbursed at a better price than night-time current which usually can be made available without any problem and at a better price in relatively large amounts.

Discharging of the storage device with the feed of electrical energy into the power supply network, that this involves, can also be used for possibly appropriately charging other vehicles with an electrical storage device, the charge condition of which has become too low, to such an extent that those vehicles can still continue to travel.

Therefore the invention also permits a plurality of vehicles to be electrically connected together, with their electrical storage devices.